## City of St. Charles, Illinois

#### Ordinance No. 2013-M-15

Ordinance Amending Title 13, "Public Utilities" Section 13.16.130 "Service Pipes – Shutoff Valves" and Section 13.20.100 "Violation – Service Discontinuance," Title 15, "Buildings and Construction" Section 107.2.5.2 "Engineering Plan" and Title 16, "Subdivisions and Land Improvements" Appendix E of the St. Charles Municipal Code


Adopted by the
City Council
of the
City of St. Charles
February 19, 2013

Published in pamphlet form by authority of the City Council of the City of St. Charles, Kane and Du Page Counties, Illinois, February 22, 2013

City Clerk

(SEAL)





## City of St. Charles, IL Ordinance No. 2013-M- 15

An Ordinance Amending Title 13, "Public Utilities" Section 13.16.130
"Service pipes – Shutoff valves" and Section 13.20.100 "Violation – Service discontinuance," Title 15, "Buildings and Construction" Section 107.2.5.2
"Engineering Plan" and Title 16, "Subdivisions and Land Improvements"

Appendix E of the St. Charles Municipal Code

WHEREAS, The City has previously approved a comprehensive amendment to Title 16, "Subdivisions and Land Improvement".

NOW THEREFORE, BE IT ORDAINED by the City Council of the City of St. Charles, Kane and DuPage Counties, Illinois as follows:

- 1. The preambles set forth hereinabove are incorporated herein as substantive provisions of this Ordinance as if fully set out in this Section 1.
- 2. That Chapter 13.16 "Water" Section 13.16.130 "Service pipes Shutoff valves" be deleted in their entirety and replaced by the following:

"Shutoff valves or curb stops shall be placed on every domestic service pipe, and shall be located between the curb line and the sidewalk line where practical, as determined by the city, but not located in driveways. Such boxes shall be so located that they are easily accessible and shall be protected from frost. Individual service lines shall be installed at locations which require a unique fire suppression service line in addition to the domestic water service line. All domestic and fire suppression service lines shall have shutoff valves installed in accordance with the City of St. Charles Engineering Design and Inspection Policy Manual."

3. That Chapter 13.20 "Cross-connection Control" Section 13.20.100 "Violation- Service discontinuance" be deleted in its entirety and replaced by the following:

"The Director of Public Works of the city is hereby authorized and directed to discontinue, after notice to the customer in the manner hereinafter provided, the water service to any property wherein any connection in violation of the provisions of this chapter is known to exist, and to take such other precautionary measures as he may deem necessary to eliminate any danger of contamination of the public water supply distribution mains. Water service to such property shall not be restored until such conditions have been eliminated or corrective action is taken in compliance with the provisions of this chapter, and until a reconnection fee in accordance with Section 13.16.040 hereof is paid to the city."

4. That Chapter 15.101 "Administration, Enforcement, Fees, and Penalties" Section 107.2.5.2 "Engineering Plan" be deleted in its entirety and replaced by the following:

Ordinance No. 2013-M- 15
Page 2 of 3

"For building permit applications that include Land Improvements as defined in Title 16 "Subdivisions and Land Improvement", an Engineering Plan shall be submitted with the Site Plan. The Engineering Plan shall be in substantial conformance to and show the necessary items identified in Title 16, "Appendix E - Drawing Requirements / Checklist - Final Engineering Plans." of the St. Charles Municipal Code."

5. That Title 16, "Subdivisions and Land Improvements" Appendix E be deleted in its entirety and replaced by the following

See Exhibit A

6. That after the adoption and approval hereof this Ordinance shall be (i) printed or published in book or pamphlet form, published by the authority of the Council, or (ii) within thirty (30) days after the adoption and approval hereof, be published in a newspaper published in and with a general circulation within the City of St. Charles.

PRESENTED to the City Council of the City of St. Charles, Kane and DuPage Counties, Illinois this 19thday of February 2013.

PASSED by the City Council of the City of St. Charles, Kane and DuPage Counties, Illinois this <sup>19th</sup>day of February 2013..

APPROVED by the Mayor of the City of St. Charles, Kane and DuPage Counties, Illinois this <sup>19th</sup>day of February 2013.

Donald P. DeWitte, Mayor

Attest:

City Clerk/Recording Secretary

COUNCIL VOTE:

Ayes: 9

Nays: O

Absent: |
Abstain:

APPROVED AS TO FORM:

City Attorney

DATE:

### Exhibit A

(Title 16, "Subdivisions and Land Improvement" Appendix E of the St. Charles Municipal Code)

## CHECKLISTS

# DRAWING REQUIREMENTS / CHECKLIST <u>Preliminary Engineering Plans</u>



Name of Subdivision	Date of Submission

NOTE: To properly execute this checklist, the developer or his engineer shall:

- 1. Insert the required information.
- 2. Denote compliance with applicable ordinances by placing his initials in all spaces where applicable.
- 3. Denote those items, which the Subdivider considers "not applicable" to this particular subdivision by checking the box marked "N/A."

#### Format/Cover Sheet:

ITEMS TO BE INCLUDED		I	ed	
			No	N/A
1.	Appropriate number of copies of preliminary plan submitted			
2.	Plans are prepared on 24-inch by 36-inch sheets			
3.	Plan scale is not less than 1" to 50'			
4.	Minimum profile scale is 1" to 50' horizontal and 1" to 10' vertical			
5.	A title sheet is included with each set of preliminary plans			
6.	Name of proposed subdivision is shown			
7.	Location given by town, range, section, or other legal description			
8.	Name and address of owner, trust, corporation or Subdivider having control			
	of project is shown	Ш	ш	L
9.	Name and seal of registered engineer or surveyor who prepared topographic			
	survey is shown	ш	Ш	
10.	Name and address of the designer of the plan is shown			
11.	North direction is shown			
12.	Date of preparation and date of revision, if any, is shown			
13.	A location map is included indicating			
h1	A. A scale of not less than 1" to 1000'			
	B. Use of surrounding land			
	C. Ownership of the surrounding land			
	D. Alignment of existing streets			
	E. Section and corporate lines			
14.	Boundary line of proposed subdivision is clearly shown			

ITEMS TO DE INCLUDED	Included				
ITEMS TO BE INCLUDED	Yes	No	N/A		
15. Total approximate acreage is shown					
16. Existing zoning classification is indicated					
17. Include the following <i>Existing</i> information within subdivision boundaries and up to 100' outside of the subdivision boundary					
<ul> <li>A. Previously platted streets and other rights-of-way, with improvements, if any, indicating</li> </ul>					
1. Location					
2. Widths					
3. Names					
B. Railroad rights-of-way, indicating					
1. Location					
2. Dimensions					
C. Utility rights-of-way, indicating					
1. Location					
2. Width	. 🔲				
3. Types					
a. Sewer					
b. Water					
c. Gas					
d. Telephone/ Communications					
e. Electric					
f. Other					
D. Parks and other open spaces indicating:					
1. Location					
2. Area					
E. Easements, indicating:					
1. Location					
2. Width					
3. Purpose (i.e. utility, drainage, stormwater, etc.)					
F. Permanent buildings and structures, indicating:					
1. Location					
2. Setback lines					

	ITEMS TO BE INCLUDED		I	nclud	ed
			Yes	No	N/A
	3.	Name of owners			
G.	Sec	tion and corporate lines			
Н.	San	itary Sewers, indicating:			
	1.	Location			
	2.	Size			
	3.	Manholes			
	4.	Material			
	5.	Invert elevation at manholes			
I.	Wa	ter mains, indicating:			
	1.	Location			
	2.	Size			
	3.	Material			
	4.	Valves, indicating:			
		a. Valve manhole, or			
		b. Valve box			
	5.	Fire hydrants and auxiliary valves			
J.	Cul	verts, indicating:			
	1.	Туре			
	2.	Location			
	3.	Size			
	4.	Material			
	5.	Invert elevations			
J.	Sto	rm sewers, indicating:			
	1.	Location			
	2.	Size			
	3.	Material			
	4.	Catchbasins			
	5.	Invert elevations			
L.	Wa	tercourses, indicating:			
	1.	Туре			
		High-water location and elevation			
	3.	Width of easement			
	4.	Location of easement			

	Iı	nclud	ed
ITEMS TO BE INCLUDED	Yes	No	N/A
5. Dimensions			
6. FEMA floodplain			
7. FEMA base flood elevations			
M. Monuments and survey markers, indicating:			
1. Location			
2. Type			
18. Topographic data is given in feet above mean sea level within the tract and			
to a distance of 100' beyond, indicating:	Ш		الا
A. Existing contours at vertical levels of not more than 2'			
B. Bench mark, indicating:			
1. Location			
2. Description			
3. Elevation			
19. Soil Sampling and Testing reports used for compliance with IEPA & CCDD			
20. Soil bearing data is given, if required by Development Engineering,			
indicating		ш	ш
A. Location of Tests			
B. Depth of Tests			
C. Soil bearing Capacity			
D. Moisture content			
21. Include the following <i>Proposed</i> information within subdivision boundaries			
and up to 100' outside of the subdivision boundary	السا		
A. Layout of streets, indicating:			
1. Street type, (i.e. Estate, Local, Collector, Arterial)			
Right-of-way width per Engineering Design and Inspection Policy  Manual			
Roadway width per Engineering Design and Inspection Policy  Manual			
4. Through street shown extended to boundaries of subdivision			
5. Cul-de-sac street design per Engineering Design and Inspection	——————————————————————————————————————		——————————————————————————————————————
Policy Manual			
6. Stormwater runoff pattern on paving			
B. Names of streets:			

	Lı	nclud	ed
ITEMS TO BE INCLUDED	Yes	No	N/A
1. Not duplicating the name of any street heretofore used in the City or			
its environs, unless the street is an extension of any already existing			
street, in which case the name shall be used			
C. Street improvement plan including truck turning template.			
D. Utility easements			
1. 10' wide around perimeter of each lot, side yard may be reduced to			L L
5' where the side lot line of a detached single-family residential lot			П
abuts the side lot line of another detached, single-family residential		_	
2. Purpose is indicated	П	$\Box$	П
E. Centerline profiles of all streets showing compliance with minimum and		<u> </u>	
maximum gradients identified in the Engineering Design and Inspection			$\Box$
Policy Manual		<u></u>	ш
G. Block layout, indicating			П
Blocks do not exceed 1200' in length	<u> </u>	-	
2. Blocks over 900' long include pedestrianways at approximate center		<u> </u>	
and/or additional access ways to parks, schools, etc.			
H. Lot layout, indicating			
	_ H		
1. Lot dimensions comply with Zoning Ordinance (Title 17)			
2. Lot areas comply with Zoning Ordinance (Title 17). Areas may be			
listed by schedule.	<del></del>		
3. Building setback lines shown and properly dimensioned	<u> </u>	<u> </u>	
4. Proposed land use		_ <u> </u> _	
5. Lot numbers	<u> </u>	_닏	_닏_
6. Lots are as nearly rectangular in shape as is practicable	_ 니_	<u> </u>	<u> </u>
7. Lot lines are substantially at right angles to the street lines and radial			
to curved street lines			<del></del>
8. Double frontage lots only where lots back upon an arterial street and			
front on an access street			
a. Additional depth allows screen planting along arterial frontage		<u> </u>	
13. Additional depth for lots abutting watercourse, drainage way,			
channel, wetland, or stream			
14. Due regard for natural features, such as:	Ц_		
a. Trees	_ <u>_</u> _	ᆜ	ᆜ
b. Watercourses			_ <u>U</u> _
c. Historic items		$\Box$	

ITEMS TO DE INCLUDED	Ir	ıclud	ed
. ITEMS TO BE INCLUDED	Yes	No	N/A
d. Other similar conditions			
Areas intended to be dedicated for public use, indicating:			
I. School sites, indicating:			
Parks / public areas conform to the Comprehensive Plan			
2. Acreage			
J. School sites, indicating:			
1. Location			
2. Dimensions			
3. Acreage			
K. Topographic information, indicating:			
1. Proposed changes in elevation, 2' minimum contours			
2. Stormwater storage facilities			
3. Normal water level (NWL)			
4. High water level (HWL)			
5. Emergency overflow elevation			
6. Storage volumes			
7. Overflow routes			
L. Sanitary sewer layout, indicating:			
1. Location			
2. Size			
3. Invert elevations at manholes			
4. Manhole locations			
5. Service locations and connections			
M. Water main layout, indicating:			
1. Location			
2. Size			
3. Fire hydrants spaced per requirements in Engineering Inspection and			
Policy Manual		Ш	Ш
4. Service locations and connections			
N. Storm sewer layout, indicating:			
1. Location			
2. Catchbasins spaced per requirements in Engineering Inspection and			
Policy Manual	Ш	Ш	Ш
3. Stormwater is not carried across or around any intersection			
4. Surface water drainage pattern for each individual lot and block			

	ITEMOTO DE IN	CLUDED		It	ıclud	ed
	ITEMS TO BE INCLUDED		Yes	No	N/A	
O. Street light lay	out, indicating:	· · · · · · · · · · · · · · · · · · ·				
1. Locations	and typical street light of	detail, or				
2. Statement	by Subdivider that stree	et lights will be install	ed in			
accordance	with City standards			لــا	Ш	
22. Typical street cros	s section, showing base	construction, surfaci	ng, concrete			
curb and sidewalk	per the Engineering De	esign and Inspection P	olicy Manual		Ш	اليا.
23. Sidewalks are show	wn					
24. Indication on draw	ings or by certificate th	nat Subdivider is awar	e of his			
responsibility for i	nstallation of street sign	ns, and for seeding and	d tree			
planting in all park	tways					
25. Stormwater Manag	gement Report					
A. Narrative						
B. Methodology						
C. Required volu	me and proposed volun	nes				
D. Existing releas	e rate and proposed rel	ease rate				
E. Overland flow	route water surface ele	evations				
F. Watershed and	sub-watershed delinea	ation				
G. Basin sizing ca	lculations	111 1 111111111111111111111111111111111				
H. Release structu	re / restrictor design ca	alculations				
I. Wetland inven	tory and Wetland Delir	neation				
Completed by:	Name	Reviewed by: _	Name			
_	Title	_	Title	<del></del>	_	
	Organization / Company		Organization / (	Compan	<b>y</b>	
	Date		Date			



## DRAWING REQUIREMENTS / CHECKLIST <u>Final Engineering Plans</u>

PLEASE NOTE: These requirements are needed for Final Engineering Plans and are in addition to Preliminary Engineering Plan Drawing Requirements

	ar	e in	addition to Preliminary Engineering Plan Drawing Requ	uirem	ents	
			Name of Subdivision Date of Submission	n		
NO	OTE:	То 1.	properly execute this checklist, the developer or his engineer shall: Insert the required information.			,
		2.	Denote compliance with applicable ordinances by placing his initi where applicable.	als in a	II spa	ces
		3.	Denote those items which the Subdivider considers "not applicable particular subdivision by the abbreviation "N.A."	e" to th	is	
<u>Fo</u>	rmat /	'Cov	er Sheet:			
			ITEMS TO BE INCLUDED	I Yes	nclud No	led N/A
1.			een submitted within 12 months of the date of approval by the City f the preliminary plan			
2.			on 24-inch by 36-inch sheets.			

ITEMS TO BE INCLUDED	11	nclud	ea
ITEMS TO BE INCLUDED	Yes	No	N/A
1. Plat has been submitted within 12 months of the date of approval by the City Council of the preliminary plan			
2. Plans are on 24-inch by 36-inch sheets.			
3. A title sheet is included with each set of plans, and includes:			
4. Name of the subdivision and unit number,			
A. Type of work covered,			
B. Location map showing relation of area to be improved to streets,			
C. An index of sheets			
D. A summary of quantities			
E. Name, address, and seal of registered engineer preparing the plans			
F. Date of preparation and revisions, if any, is shown			
5. Plan and profiles include			
A. Horizontal scale is no less than 1 inch to 50 feet			
B. Vertical scale is no less than 1 inch to 5 feet			
6. Cross sections are submitted as necessary to indicate feasibility of proposed street elevations in relation to adjacent lot elevations, and include sidewalk location			
A. Horizontal and vertical scales are no less than 1 inch to 10 feet			

ITEMS TO DE INCLUDED			ed
ITEMS TO BE INCLUDED	Yes	No	N/A
7. North direction is shown for each separate plan view			
8. An adequate number of bench marks are shown with elevations referenced to			
mean sea level, and the City's Geodetic Control Network to facilitate			
checking of elevations without more than one setup of a surveyor's level			
9. Delineation is shown of all easements necessary to serve all lots with underground and overhead utilities, and to allow for perpetual maintenance			
of these facilities	لا	ш	LJ
Sanitary Sewer Improvements:			
10. An authorized Illinois Environmental Protection Agency Permit for the			<u></u>
sanitary sewer extension accompanies the plans	Ш	ш	
11. Sanitary sewer plans and specifications are complete and conform to the			
standards and requirements of City of St. Charles Engineering Design and	П		П
Inspection Policy Manual as revised or superseded and denote all of the			
following:  A. All properties in the subdivision are served and house service	·		
connections are provided,			
B. The proposed pipe sizes			
C. The plan conforms to the overall City plan for any trunk sewers			
traversing the subdivision,		لسا —	
D. The distance between manholes is not exceeded,	Ш		
E. The invert elevation of each manhole is shown,			
F. The grade of each section of sewer is shown by percentage in accordance	П		
with accepted engineering practice,			
G. Proposed pipe materials,	<u> </u>	<u>Ц</u>	Ц
H. Profile of existing and proposed ground surfaces,		<u> </u>	Щ
I. Risers are shown for individual house service laterals where needed,			Ш
J. Pipe joints are of permitted type,			
K. Specifications include provisions for checking of infiltration or			
exfiltration,  L. Standard details are shown and include:	_	<u> </u>	<u> </u>
L. Standard details are shown and include:  1. Standard manhole	片	<u> </u>	<u> </u>
	<u> </u>	ᆜ	ᆜ_
2. Drop manhole	<u> </u>	ᆜ	<u> </u>
3. Standard riser		Ц	
4. Standard service installation	Ш	Ш	

	Ii	led	
ITEMS TO BE INCLUDED	Yes	No	N/A
Water main Improvements:			
12. An authorized Illinois Environmental Protection Agency permit for the water main installation accompanies the plans;			
13. Water distribution plans and specifications are complete and conform to City of St. Charles Engineering Design and Inspection Policy Manual as revised or superseded, and include all of the following:			
A. All properties in the subdivision are served and provisions are made for service connections within the property lines,			
B. The proposed pipe sizes,			
C. The plan conforms to the City's overall plan for any trunk lines which might traverse the subdivision,			
D. Valve and hydrant spacing and location conform to the approved preliminary plan,			
E. Material and joint specifications comply with the City's standards,			
F. Specifications include provisions for testing and sterilization of all new water distribution facilities,			
G. Standard details are shown and include the following:			
1. Valve manhole			
2. Standard cover			
3. Standard hydrant installation			Ō
Roadway, Storm Sewer, & Grading Improvements:			
14. Street plans, including storm sewers, are complete and conform to the City of St. Charles Engineering Design and Inspection Policy Manual as revised or superseded, and include all of the following:			
A. The location of streets and width of pavements conform to those indicated on the approved preliminary plan			
B. Plan shows curb, gutter and sidewalk locations, and include the following information:			
1. Corner curb radius			
2. Curve data for all horizontal curves and tangents			
3. Direction of flow along all curbs			
<ol> <li>No surface water is carried across or around any street intersection, or for a distance greater than 600 feet.</li> </ol>			
C. Cross sections as necessary to identify proposed street elevations in relation to adjacent lot and sidewalk elevations			

	Included		
ITEMS TO BE INCLUDED	Yes	No	N/A
Catchbasin invert elevations			
2. The proposed pipe sizes			
3. The grade of each section of sewer is shown by percentage in accordance with accepted engineering practice			
4. Storm sewer elevations do not conflict with any other underground utilities			
5. Storm sewer is connected with an adequate outfall			
6. Curve data is given for vertical road curves,			
D. The storm sewer system is designed to provide sufficient capacity for the draining of upland areas contributing to the storm water runoff on the street			
<ol> <li>Storm sewer design computations are submitted with plans</li> </ol>			
E. A surface water drainage pattern is shown for each block			
F. Material specifications comply with City standards and include:			
1. Paving base materials			
2. Paving surface materials			
3. Concrete			
4. Pipe materials			
G. Cross sections for each street type that include the following:			
1. Pavement construction			
2. Concrete curb and gutter			
3. Concrete sidewalk			
15. Street light plans are complete and conform to City standards as identified in Title 12.30- Street Improvements or as revised or superseded, and include the following:			
A. Pole locations,			
B. Spacing,			
C. Average maintained foot-candle illumination (calculated),			
D. Control system and wiring diagram,			
E. Typical section showing:			
1. Type of base and pole			
2. Bracket or arm			
3. Luminaire, indicating type of lamp and wattage			
4. Mounting height			

ITEMS TO BE INCLUDED		Included		
		No	N/A	
16. Parkways improvements				
A. Removal of stumps, trees that cannot be saved, boulders, and similar items,	all other			
B. Grading, installation of topsoil, and seeding or sodding,				
C. Planting of trees				
17. Street signs are shown to be installed, at all street intersect previously marked, in accordance with The City of St. Charles Eng Design and Inspection Policy Manual as revised or superseded.				
Stormwater Management:				
18. Stormwater Management Report				
A. Narrative				
B. Methodology				
C. Required volume and proposed volumes				
Stage storage chart on detention pond grading plan id elevation, proposed volume and as-built volumes	entifying			
D. Existing release rate and proposed release rate,				
E. Overland flow route water surface elevations,				
F. Watershed and sub-watershed delineation,				
G. Basin sizing calculations,				
H. Release structure / restrictor design calculations,				
I. Wetland inventory and Wetland Delineation				
Completed by: Reviewed by:	Name			
nume	runt			
Title	Title			
Organization / Company Org	ganization / Company	<del>,</del>		
Date	Date			

# DRAWING REQUIREMENTS / CHECKLIST Record Drawings (As-built Drawings)

THE RECORD DRAWINGS SHALL BE PREPARED BY THE ORIGINAL DESIGN ENGINEER AND INCLUDE THE COMPLETE SET OF APPROVED FINAL ENGINEERING DRAWINGS AND SHALL INCLUDE THE FOLLOWING INFORMATION:

General:

	<del></del>
	All sheets in approved Final Engineering Drawings shall be submitted and labeled as "Record Drawings" and dated.
0	One (1) paper set of as-built drawings shall be submitted for review and comment.  Once the as-built plans are approved  One (1) CD containing all electronic AUTOCAD (.dwg) or Microstation (.dgn) design file drawings,  One (1) set of signed and sealed mylars of approved as-built drawings, and  One (1) paper set of signed and sealed of approved as-built drawings for final record keeping shall be submitted.
	Plans shall be signed and sealed by a Registered Professional Engineer with the following certificate.  STATEMENT OF OPINION
	Pursuant to the St. Charles Municipal Code, I
a r	egistered Professional Engineer in the State of Illinois, hereby declare that these "Record
Dr.	awings" pertaining to (water main, sanitary sewer, storm sewer) (storm water management) and
inc	cluded herewith, have been prepared for a certain project know as
	and contain information as obtained by the surveyor, , and the contractor,
Dra cor	s my professional opinion that these "Record Drawings" adequately depict the Record awing Information required by the City of St. Charles and substantiate that the improvements instructed as part of this project will function in substantial conformance to the design intent of approved Engineering Plans.
	Dated:
	Signed:
(SI	Illinois Registration Number:EAL)
	·

14

	Plans shall note what record information is being submitted and the date of preparation.			
	All utilities shall be labeled either as "Private" or "Public". It shall be noted somewhere on the as-built plans that "Private utility mains shall not be maintained by the City of St. Charles".			
<u>St</u>	reets / Roadways:			
	T/C, center line, T/C grades at 50-foot centers.			
	Verify grading in cul-de-sacs and at curb returns/intersections by comparing proposed and existing elevations at locations shown on Final Plans.			
	Note extent of sidewalk construction at the time of drawing preparation.			
	Note whether surface course is placed at time of drawing preparation.			
Ste	Storm Sewers:			
	Note changes in alignment or size of sewers or manholes due to field changes. Cross out approved conditions and add existing conditions.			
	Rim and invert elevations for all pipes entering a structure. Cross out approved conditions and add existing information.			
	Calculate revised pipe slopes and note on the plans.			
	Denote location of stubs for sump service connections.			
<u>De</u>	tention Pond / Drainage			
	Provide as-built topography for stormwater management basins (one {1} foot contour).  Complete stage storage chart on the stormwater management basin as-built that compares the proposed stage storage volumes with as-built volumes.			
	Verify restrictor size and elevation. Cross out approved conditions and add existing conditions.			
	Verify emergency overflow size and elevation. Cross out approved conditions and add existing conditions.			

	Verify overflow swales and major drainage route grading by comparing approved and existing spot elevations.
	Provide revised calculations, includes modeling of As-built conditions, for any variances to the approved Final Engineering plans depicting that minimum detention volumes have been obtained or exceeded.
<u>Sa</u>	nitary Sewers:
	Note changes in alignment or size of sewers or manholes due to field changes. Cross out approved conditions and add existing conditions.
	Rim and invert elevations for all pipes entering a structure. Cross out approved conditions and add existing information.
	Calculate revised pipe slopes and note on the plans. Note size and location of services with a distance to nearest manhole.
W	ater Main:
	Note changes in alignment or size of mains due to field changes. Cross out approved conditions and add existing conditions.
	Rim and top of pipe elevations for all pipes entering a structure. Cross out approved conditions and add existing information.
	Note size and location of B-Boxes with two (2) physical ties to (in order of preference):  a) An above-ground physical element, i.e., fire hydrant, light pole, building corner.  b) A manhole or Valve Vault.  c) Property corners.
Ele	ectric:
	Location of streetlights and routing of cables feeding to transformers or secondary pedestals.
<u>Ot</u>	her Utilities (Gas, Phone, Cable):
	Location and routing of utilities servicing development.

State of Illinois	)	
	)	SS
Counties of Kane and DuPage	)	

## Certificate

I, NANCY GARRISON, certify that I am the duly elected and acting Municipal City Clerk of the City of St. Charles, Kane and DuPage Counties, Illinois.

I further certify that on February 19, 2013, the Corporate Authorities of such municipality passed and approved Ordinance No. 2013-M-15, entitled

"Ordinance Amending Title 13, "Public Utilities"
Section 13.16.130 "Service Pipes – Shutoff Valves" and
Section 13.20.100 "Violation – Service
Discontinuance," Title 15, "Buildings and
Construction" Section 107.2.5.2 "Engineering Plan"
and Title 16, "Subdivisions and Land Improvements"
Appendix E of the St. Charles Municipal Code,"

which provided by its terms that it should be published in pamphlet form.

The pamphlet form of Ordinance No. 2013-M-15, including the Ordinance and a cover sheet thereof was prepared, and a copy of such Ordinance was posted in the municipal building, commencing on February 22, 2013, and continuing for at least ten days thereafter. Copies of such Ordinance were also available for public inspection upon request in the office of the municipal clerk.

DATED at St. Charles, Illinois, this \_\_\_\_19th\_\_ day of February 2013.

Municipal Clerk